

#### 6. Accidental Release Measures:

Dike and contain spill with inert material (sand, earth, etc.). Collect spill with a mop, absorbent material (example: floor-dry) or vacuum. Thoroughly rinse affected area with water.

7.	Handling and Storage:Handling:Keep from freezing. Keep out of reach of children.Storage:Maintain Temperature Minimum 40°F (4°C) - Maximum	n 100°F (38°C)		
8.	Exposure Controls / Personal Protection: Exposure Limits Ingredients Dipropylene Glycol Methyl Ether Isopropanol Exposure Controls Engineering Controls: Normal good ventilation is sufficient Personal Protective Equipment: Eye Protection: Approved Safety Goggles or Glasses Skin Protection: Chemical Resistant Rubber Gloves Respiratory Protection: Not required, Avoid breathing spra	CAS Number 34590-94-8 y mist	Osha PEL 100 ppm	ACGIH TLV 100 ppm
9.	Physical and Chemical Properties: Physical State: Liquid Appearance: Blue Odor: Pleasant Solubility: Complete Evaporation Rate: NA Vapor Pressure (MM HG): NA Vapor Density (Air = 1): > 1	pH: 8-9 Specific Gravity (H2O = 1): Flammability: None Flash Point: None Boiling Point: > 212° F (100 %volatile: 82%		
10.	Stability and Reactivity:   Chemical Stability:   Stability of Hazardous Reactions:   None are known   Incompatability (Materials to Avoid):   None are known   Hazardous Decomposition or By-products:   None   Hazardous Polymerization:   Will not Occur   Conditions to Avoid:			
11.	Toxicological Information:   Signs and Symptoms of Overexposure: Causes irritation on contact   Acute Effects:   Eye Contact: Causes irritation on contact   Skin Contact: Causes mild irritation on prolonged or repeated contact   Inhalation: None Known   Ingestion: May be harmful if swallowed   Target Organ Effects: Central nervous system, Liver, Kidneys, Respiratory tract, Ears   Chronic Effects: May cause damage to central nervous system, respiratory tract, ears, and/or kidneys, liver through prolonged or repeated exposure.   Acute Toxicity Values: Oral LD 50 > 5000 mg/kg   Dermal LD 50 > 5000 mg/kg   Inhalation (Vapor) LC 50 Vapors Considered Non-Toxic			
12.	Ecological Information: Persistence and Degradability: Not Available Bio Accumulative Potential: Not Available Mobility in Soil: Not Available Aquatic Toxicity: Not Available			

# 13. Disposal Considerations:

Solution may contain zinc. For material not used in normal use , Coagulate with ferric chloride or sulfate and then lime. Decant the clear liquid to a sanitary sewer. Dispose of the coagulum by sanitary landfill or incinerator. Follow all existing pollution control ordinances.

# 14. Transportation Information:

UN Number: None Shipping Name: Buffing or Polishing Compound Transport Hazard Class: None Packing Group: None Marine Pollutant: NO

### 15. Regulatory Information:

TSCA Status: All ingredients listed Clean Water Act: None of the chemicals in this product are listed under the CWA Clean Air Act: Glycol Ethers (Diethylene Glycol Monoethyl Ether(111-90-0)) is listed as a hazardous air pollutant (HAP) CERCLA Reportable Quantity: None SARA Title III Information: Section 302 Extremely Hazardous Chemicals: None Listed Section 311 / 312 Hazard Category: Immediate Health Section 313 Toxic Chemicals: Glycol Ethers (Diethylene Glycol Monoethyl Ether (111-90-0)) State Regulations: None International Regulations: WHMIS Controlled Product Hazard Class: D2B

## 16. Other Information:

Prepared By: Eric Scholl Telephone Number: 651-481-1900 Revision Date: 6/7/2013 Supersedes: 4/1/2012 This SDS applies to the following Part Numbers

904923

The information contained herein is based on data considered accurate; however no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The company assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

