



KENDALL SUPER THREE STAR GEAR LUBRICANT, SAE  
30W-85W-140

Product Code: K51 7721

=====

FIRE AND EXPLOSION DATA---SECTION III

=====

Special Fire Fighting Procedures:

Do not use water except as fog.

Unusual Fire and Explosion Hazards:

none

Flashpoint: (Method Used) Cleveland open cup greater than 200°C (390°F)

Flammable limits %: not applicable

Extinguishing agents:

Drychemical or Waterfog or CO<sub>2</sub> or Foam

Closed containers exposed to fire may be cooled with water.

=====

HEALTH HAZARD DATA---SECTION IV

=====

Permissible concentrations (air):

see COMMENTS section

Chronic effects of overexposure:

no data available

Acute toxicological properties:

no data available

Emergency First Aid Procedures:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: Contact a physician immediately.

=====

SPECIAL PROTECTION INFORMATION---SECTION V

=====

Ventilation Type Required (Local, mechanical, special):

see COMMENTS section

Respiratory Protection (Specify type):

Use NIOSH/MSHA certified respirator with organic vapor cartridge if vapor concentration exceeds permissible exposure limit

Protective Gloves:

neoprene type

Eye Protection:

chemical safety goggles

Other Protective Equipment:

none

(Continued on next page)

W I T C O M A T E R I A L S A F E T Y D A T A S H E E T

KENDALL SUPER THREE STAR GEAR LUBRICANT, SAE  
-85W-140

PAGE 3

Product Code: K51 7721

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up:

Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand, or vermiculite. Sweep up and dispose as solid waste in accordance with local, state, and federal regulations.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local regulations.

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage:

Do not handle or store at temperatures over

Maximum Storage Temperature: 38°C (100°F)

TRANSPORTATION DATA---SECTION VIII

D.C.T.: Not Regulated

Portable Quantity: not applicable

Weight Classification: Petroleum Lubricating Oil

Special Transportation Notes:

none

COMMENTS

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m3 for mineral oil mist (OSHA and ACGIH).

\* STATE REGULATORY INFORMATION:

Pennsylvania Worker And Community Right To Know Act: This product contains the following ingredient(s).

Hydrocarbon oils CAS NO. 8020-83-5

The additive mixtures in this product have been declared a trade secret by the additive manufacturers.

Prepared by: Robert Kellam

Title: Group Supervisor, Lubricants Testing, Maintenance, and Safety

Original Date: 05/26/81 Sent to: \_\_\_\_\_

Revision Date: 04-05-90 \_\_\_\_\_

Supersedes: 08-11-89 \_\_\_\_\_

Date Sent: \_\_\_\_\_

(Continued on next page)

W I T C O M A T E R I A L S A F E T Y D A T A S H E E T

KENDALL SUPER THREE STAR GEAR LUBRICANT, SAE  
80W-85W-140

PAGE 4

Product Code: K51 7721

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.