

SILICONE SPRAY

M914C, M914/6C

MSDS Revision Date (mm/dd/yyyy): 07/15/2010

Page 1 of 7

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier : **SILICONE SPRAY**

Product Use : Lubricant.

Chemical Family : Mixture.

Manufacturer part no. : M914C, M914/6C

Supplier's name and address:

Radiator Specialty Co., of Canada

1711 Aimco Blvd.
Mississauga, ON, Canada
L4W 1H7

Manufacturer's name and address:

Refer to Supplier

Information Telephone # : (905) 625-9117 (Monday - Friday, 9AM - 5PM)

24 Hr. Emergency Tel # : (613) 996-6666 (CANUTEC)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR).

WHMIS classification:

Class A (Pressurized containers);

Class B5 (Flammable Aerosols);

Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);

Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

Labelling: Phrases recommended to appear on a supplier label, can be found in Section 15.

WHMIS symbols required on a supplier label:



Emergency Overview : Clear to yellow liquid, contained in a pressurized aerosol can. Petroleum odour. DANGER! Flammable aerosol. Contents under pressure. Container may explode if heated. Harmful if inhaled. May be harmful if absorbed through the skin. May be harmful or fatal if swallowed. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. May be an aspiration hazard. May cause skin irritation. Contains material which may cause cancer, based on animal data. Possible birth defect hazard - contains material that may cause birth defects, based on animal data.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.

Skin : May cause moderate skin irritation. May be absorbed and cause symptoms similar to those for inhalation. If product is sprayed directly on skin, symptoms of frostbite may be experienced including numbness, prickling and itching.

Eyes : May cause mild eye irritation. If product is sprayed directly into the eyes, could cause freezing of the eye.

Ingestion : May cause irritation of mouth, throat, and stomach. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Material is an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Effects of long-term (chronic) exposure

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Carcinogenic status : Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : May cause birth defects. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects : See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt. %</u>
stoddard solvent	8052-41-3	40.00 - 70.00
Petroleum distillate	64742-47-8	10.00 - 30.00
1,2,4-Trimethylbenzene	95-63-6	3.00 - 7.00
1,3,5-Trimethylbenzene	108-67-8	3.00 - 7.00
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	3.00 - 7.00
Dimethylpolysiloxane	63148-62-9	3.00 - 7.00
Carbon dioxide	124-38-9	3.00 - 4.00
Xylene	1330-20-7	1.00 - 5.00
Ethylbenzene	100-41-4	0.10 - 1.00

SECTION 4 - FIRST AID MEASURES

Inhalation	: Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
Skin contact	: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Get medical attention.
Eye contact	: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek prompt medical attention.
Ingestion	: Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person.
Notes For Physician	: Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability	: Flammable aerosol. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time. Vapours may be heavier than air and may collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface.
Oxidizing properties	: None known.
Explosion data: Sensitivity to mechanical impact / static discharge	: May be sensitive to static discharge. Aerosols are sensitive to mechanical impact. Contents under pressure.
Suitable extinguishing media	: Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.
Special fire-fighting procedures/equipment	: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Shield personnel to protect from venting or rupturing containers.
Hazardous combustion products	: Carbon oxides; Aldehydes; Hydrocarbons; nitrogen oxides (NOx); Sulphur oxides; Phosphorus compounds; silicon oxides; Polycyclic aromatic hydrocarbons; other unidentified organic compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions	: All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.
Environmental precautions	: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

- Spill response/cleanup** : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Do not puncture or incinerate containers. Avoid contact with incompatible materials. Wash thoroughly after handling.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Do not eat or smoke in areas of use or storage.
- Incompatible materials** : Strong oxidizing agents; Acids; Bases.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

Ingredients	ACGIH TLV		OSHA PEL	
	TWA	STEL	PEL	STEL
stoddard solvent	100 ppm	N/Av	500 ppm	N/Av
Petroleum distillate	200 mg/m ³	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	*25 ppm	N/Av	*25 ppm (final rule limit)	N/Av
1,3,5-Trimethylbenzene	*25 ppm	N/Av	*25 ppm (final rule limit)	N/Av
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ (As 'Oil mist, mineral')	N/Av	5 mg/m ³ (As 'Oil mist, mineral')	N/Av
Dimethylpolysiloxane	N/Av	N/Av	N/Av	N/Av
Carbon dioxide	5000 ppm	30,000 ppm	5000 ppm	N/Av
Xylene	100 ppm	150 ppm	100 ppm	N/Av
Ethylbenzene	100 ppm	125 ppm	100 ppm	N/Av

*Note:: The OSHA PEL's and ACGIH TLV's listed above for 1,2,4-Trimethylbenzene and 1,3,5-Trimethylbenzene are for 'Trimethylbenzene (mixed isomers)'.

Ventilation and engineering measures

- : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

- : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection

- : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye / face protection

- : Chemical splash goggles are recommended.

Other protective equipment

- : Depending on conditions of use, an impervious apron should be worn. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

- : Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink, smoke or use cosmetics while working with this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid aerosol.	Appearance	: Clear to yellow liquid.
Odour	: Petroleum odour.	Odour threshold	: N/Av
pH	: N/Av		
Boiling point	: 154.4°C	Specific gravity	: 0.81

Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av
Vapour pressure (mmHg @ 20° C / 68° F)	: N/Av	Solubility in water	: insoluble
Vapour density (Air = 1)	: N/Av	Evaporation rate (n-Butyl acetate = 1)	: N/Av
Volatile organic Compounds (VOC's)	: N/Av	Volatiles (% by weight)	: 58.17%
Flash point	: 53.33°C (concentrate)	Auto-ignition temperature	: N/Av
Flash point Method	: TCC	Upper flammable limit (% by vol.)	: N/Av
Lower flammable limit (% by vol.)	: N/Av	Flashback observed	: NO
Flame Projection Length	: 35.56 cm	Viscosity	: 16 cp @ 21.1°C (concentrate)
Absolute pressure of container	: N/Av		
General Information	: No additional information.		

Section 10: STABILITY AND REACTIVITY

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed.
Hazardous polymerization	: Hazardous polymerisation does not occur.
Conditions to avoid	: Avoid heat and open flame. Ensure adequate ventilation, especially in confined areas. Keep out of direct sunlight.
Materials To Avoid And Incompatibility	: See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products	: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, digestive system, central nervous system.
Routes of exposure	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> YES <i>Skin & Eyes:</i> YES <i>Ingestion:</i> YES
Irritancy	: Moderate skin irritant. Mild eye irritant.
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

Ingredients	LC₅₀(4hr)	LD₅₀	
	inh, rat	(Oral, rat)	(Rabbit, dermal)
stoddard solvent	> 5500 mg/m ³	> 5000 mg/kg	> 3000 mg/kg
Petroleum distillate	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	18,000 mg/m ³	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethylbenzene	24,000 mg/m ³	23,000 mg/kg	N/Av
Distillates (petroleum), hydrotreated heavy naphthenic	2180 mg/m ³ (mist)	> 5000 mg/kg	> 2000 mg/kg
Dimethylpolysiloxane	N/Av	> 2000 mg/kg	> 19,400 mg/kg
Carbon dioxide	N/Av	N/Av (gas)	N/Av (gas)
Xylene	6350 ppm	4300 mg/kg	> 5 mL/kg
Ethylbenzene	4000 ppm	3500 mg/kg	15,380 mg/kg

Carcinogenic status	: Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3). Contains the following chemicals listed as confirmed animal carcinogens (A3) by ACGIH: Petroleum distillates.
Reproductive effects	: Not expected to cause reproductive effects.
Teratogenicity	: This product contains Xylene. Xylene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.
Mutagenicity	: Not expected to be mutagenic in humans.
Epidemiology	: None known or reported by the manufacturer.

- Sensitization to material** : Not expected to be a skin or respiratory sensitizer.
Synergistic materials : None known or reported by the manufacturer.
other important hazards : CNS depression may result from extreme exposures.
Conditions aggravated by overexposure : Pre-existing skin, eye and respiratory disorders.


SECTION 12 - ECOLOGICAL INFORMATION

- Ecotoxicity** : The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
Mobility : No data is available on the product itself.
Persistence : No data is available on the product itself.
Bioaccumulation potential : No data is available on the product itself.
Other Adverse Environmental effects : No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Do not puncture or incinerate containers.
Methods of Disposal : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	none	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, if shipping under this exemption.				

SECTION 15 - REGULATORY INFORMATION

Labelling:

DANGER! Flammable aerosol. Contents under pressure. Container may explode if heated. Harmful if inhaled. May be harmful if absorbed through the skin. May be harmful or fatal if swallowed. May cause nausea, vomiting, headache and other central nervous system effects. May cause respiratory irritation. May be an aspiration hazard. May cause skin irritation. Contains material which may cause cancer, based on animal data. Possible birth defect hazard - contains material that may cause birth defects, based on animal data.

Precautions: Use in a well-ventilated area. Wear suitable protective equipment during handling. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Do not puncture or incinerate containers. Avoid contact with incompatible materials. Wash thoroughly after handling. Store in a cool, dry, well-ventilated area away from sources of heat, ignition and sunlight

FIRST AID: If inhaled, move to fresh air. If breathing stopped, begin artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention. For skin contact, wash with soap and water while removing contaminated clothing. Get medical attention. For eye contact, flush with running water for at least 15 minutes. If irritation persists, seek prompt medical attention. If ingested, do not induce vomiting. Never give anything by mouth to an unconscious person. Seek immediate medical attention/advice.

Refer To Material Safety Data Sheet for further information.

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Refer to Section 2 for a WHMIS Classification for this product.


This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

SECTION 16 - OTHER INFORMATION

Legend	: ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstract Services CNS: Central Nervous System HSDB: Hazardous Substances Data Bank IARC: International Agency for Research on Cancer Inh: Inhalation LC: Lethal Concentration LD: Lethal Dose MSHA: Mine Safety and Health Administration N/Ap: Not Applicable N/Av: Not Available NIOSH: National Institute of Occupational Safety and Health NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit RTECS: Registry of Toxic Effects of Chemical Substances STEL: Short Term Exposure Limit TCC: Tagliabue Closed Cup TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TWA: Time Weighted Average WHMIS: Workplace Hazardous Materials Identification System
References	: 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2010. 2. International Agency for Research on Cancer Monographs, searched 2010. 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2010 (Chempendium, HSDB and RTECs). 4. Material Safety Data Sheets from manufacturer.

<p>Prepared for: Radiator Specialty Co. of Canada 1711 Aimco Blvd. Mississauga, ON, Canada, L4W 1H7 Telephone: 905-625-9117 (Mon. - Fri., 9 AM - 5 PM) Please direct all enquiries to Radiator Specialty.</p>	
<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Radiator Specialty Co. of Canada and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Radiator Specialty Co. of Canada expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Radiator Specialty Co. of Canada.

MSDS Preparation Date (mm/dd/yyyy)

: 07/30/2007

MSDS Revision Date (mm/dd/yyyy)

: 07/15/2010

SILICONE SPRAY

M914C, M914/6C

MSDS Revision Date (mm/dd/yyyy): 07/15/2010

Page 7 of 7

Revision No. : 2a

Revision Information : Sections 2 and 3, switched.
(M)SDS sections updated:
2. HAZARDS IDENTIFICATION;
3. COMPOSITION/INFORMATION ON INGREDIENTS;
4. FIRST AID MEASURES;
5. FIRE-FIGHTING MEASURES;
8. EXPOSURE CONTROLS / PERSONAL PROTECTION;
9. PHYSICAL AND CHEMICAL PROPERTIES;
11. TOXICOLOGICAL INFORMATION;
12. ECOLOGICAL INFORMATION;
15. REGULATORY INFORMATION.

END OF DOCUMENT

