



Way / Kete

REC'D AUG 22 2003

LPS LABORATORIES  
MSDS  
MATERIAL SAFETY DATA SHEET

Section 1 - Product Identification and Use

Manufacturer's Name:  
LPS Laboratories

Street Address:  
4647 Hugh Howell Road

City, State, Zip:  
Tucker, GA 30085-5052

Telephone Number: 770-934-7800  
Emergency Telephone Number: 1-800-424-9300 Chemtrec  
Outside U.S.: (703) 527-3887

Trade Name:  
LPS 3 Heavy-Duty Rust Inhibitor

Chemical Family:  
Petroleum Hydrocarbons

Part Numbers:  
00316, 03128, 00305, 00355  
00322 - LPS 3 Trigger Spray

Hazardous Materials Description and proper shipping name (49 CFR 172.101):  
Compound, Boiler Preserving Liquid NMFC 50093 SUB 2 BRL/BXS CL55  
CONSUMER COMMODITY ORM-D

TSCA Inventory:  
All of the ingredients are listed on the TSCA inventory.

HMIS Labeling: Health: 1  
Flammability: 2  
Reactivity: 0

Section 2 - Hazardous Ingredients / Identity Information

Ingredients	CAS Numbers	%WW	OSHA PEL	ACGIH TLV	OTHER LIMITS
Aliphatic Hydrocarbon	64742-88-7	70-80	500 ppm	100 ppm	None
Petroleum Oil (Severely hydro-treated)	64742-52-5	10-15	5mg/m3*	5mg/m3*	10 mg/m3* STEL
Dipropylene Glycol Monomethyl Ether	34590-94-8	2-3	100 ppm	100 ppm	150 ppm STEL
Carbon dioxide propellant (aerosol only)	124-38-9	2-3	10,000 ppm	5,000 ppm	30,000 ppm STEL

\* Oil mist

Section 3 - Physical / Chemical Characteristics

Boiling point (F°): 315°F  
Vapor pressure ( mmHg) @100 °F : <5  
Vapor density (Air = 1): 4.8 - 5.3  
Solubility in water: Nil  
Appearance and odor: Dark brown liquid with sweet, mild odor.

Specific gravity (H2O = 1): .830  
Percent volatile by volume (%): 75  
Evaporation rate (n-Butyl Acetate = 1): 12

Section 4 - Fire and Explosion Hazard

Flash point (method used): 112°F TCC  
Extinguishing media: Foam, dry chemical, or carbon dioxide. Do not use a direct stream of water.  
Special fire fighting procedures: Self-contained breathing apparatus should be provided to fire fighters. Water fog may be used to cool closed containers.  
Unusual fire and explosive hazards: Intensive heat created by fire will cause aerosols to burst

Flammable limits (of diluent ): LEL 0.7% UEL 6.0%

Section 5 - Health Hazard Data

Primary route(s) of entry: Inhalation eyes, skin.

N.E. = Not established  
N.A. = Not applicable

**Health hazard/effects of over exposure:**

**Inhalation:** Headache, dizziness, nausea and anesthetic effects.

**Eyes:** Irritation.

**Skin:** Repeated or prolonged contact may cause drying and defatting of skin.

**Ingestion:** Low order of oral toxicity; however minute amount aspirated into lungs during ingestion may cause severe pulmonary injury

**Medical conditions aggravated by exposure:** Pre-existing eye, skin and respiratory disorders may be aggravated.

**Chemicals listed as potential carcinogen:** NTP: No IARC: No OSHA: No

**Emergency and first aid procedures:**

**Inhalation:** Move to fresh air and contact physician. Administer oxygen if breathing is difficult.

**Eyes:** Flush eyes with plenty of water and contact physician

**Skin:** Wash with soap and water, apply medicated skin cream.

**Ingestion:** Contains aliphatic hydrocarbons and petroleum oil. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact physician immediately.

---

**Section 6 - Reactivity Data**

---

**Stability:** Stable      **Conditions to avoid:** Avoid sparks or open flames. See handling and storage precautions

**Incompatibility (Materials to avoid):** Strong oxidizing agents.

**Hazardous decomposition products:** Thermal decomposition may yield carbon monoxide.

**Hazardous polymerization:** Will not occur

---

**Section 7 - Precautions for Safe Handling and Use**

---

**Steps to be taken in case material is released or spilled:** Ventilate area by opening doors and windows. Remove ignition sources. Remove leaking container and transfer remaining product to another vessel. Prevent product from going into sewers and water sources by diking or impounding. Using appropriate safety equipment, mop up or soak up with absorbent material, such as sand or clay

**Waste disposal methods:** Dispose of in accordance with local, state and federal regulations for petroleum distillates

**RCRA Hazardous Waste No.:** This material has the RCRA characteristic of ignitability and if discarded in its purchased form would have the hazardous waste number D001

**CERCLA Reportable Quantity:** N.A.

**SARA TITLE III Chemicals:** None

**Precautions to be taken in handling and storage:** Store aerosols below 120°F and above 32°F. Store bulk below 150 F and above 32°F. Store away from ignition sources and avoid breathing vapors

---

**Section 8 - Control Measures**

---

**Respiratory Protection:** None required if good ventilation is maintained. For enclosed areas, use NIOSH approved organic vapor cartridge respirator or self-contained breathing apparatus.

**Ventilation:** Local exhaust is usually adequate. However, mechanical ventilation should be used when spraying in enclosed areas. Vapor concentration should be minimized as much as possible

**Protective gloves:** Use solvent resistant gloves for liquid handling

**Eye protection:** For spraying or splashing of solvent, use face shield or goggles

**Other protective equipment:** As necessary to prevent prolonged or repeated skin contact.

**Work/hygienic practices:** Wash hands with soap and water after use and/or before breaks, lunch and at the end of work periods. Remove contaminated clothing and launder before reuse.

---

## Section 9 - Preparation Date of MSDS

---

The foregoing technical information and recommendations are compiled from sources that are believed to be accurate and reliable. However, they are supplied without warranty or guarantee of any kind either expressed or implied. The purchaser is responsible for selecting and determining the suitability of products for purchaser's particular needs and we disclaim any responsibility for improper applications or misuse of our products in any manner whatsoever.

January 31, 2000  
Fred Fugitt, Technical Services Chemist  
Jed Williams, Manager of Research and Development  
LPS Laboratories

**ITW**

Form # 2502  
MSDS LPS 3 Heavy-Duty Rust Inhibitor