



# 6220

## PLASTIC ROOF CEMENT Data Sheet

- Stays soft & pliable
- Repairs flashings

### WHAT IS THIS AND WHERE DO I USE IT?

Black Jack 6220 is a pliable asphalt roof cement that is ideal for many roof repairs and for stopping roof leaks around vent pipes, spouts, valleys, skylights, gutters and chimneys. Use for the construction and repair of flashings. It may also be used to seal cracks in exterior chimneys, walls, foundation joints or for lining leaking gutters and troughs. Use only on dry surfaces. Plastic Roof Cement is not paintable.

### HOW DO I PREPARE THE SURFACE?

Remove dust, dirt and debris using a stiff brush or broom. Remove crusted rust or scaling previous coating by scraping or wire brushing.

On Asphalt Roofs: Replace all drawn up nails with larger nails before patching with Plastic Roof Cement.

### HOW DO I APPLY & AT WHAT THICKNESS?

Apply with trowel or putty knife. To patch small holes or breaks, fill with Plastic Roof Cement and smooth down edges. For patching larger holes and substantial breaks or joints, apply Plastic Roof Cement approximately 1/4" thick, embed fiberglass or polyester membrane into the plastic Roof Cement, and cover with another 1/4" layer of Plastic Cement. Feather edge plastic cement around patch.

During cold weather, keep this material in a heated room before using for easy workability.

### WHAT IS THE COVERAGE?

One gallon covers approximately 7 square feet at 1/4" thickness.

### HOW DO I CLEAN-UP?

Tools should be cleaned with paint thinner or mineral spirits.

### PRECAUTIONS:

Seal container when not in use. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems.

Manufactured by (Manufacturado por):  
P.O. Box 5449, Tampa, FL 33675  
www.gardner-gibson.com  
© 2008 Gardner-Gibson, Inc.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Flash Point	105°F (41°C)
Weight Per Gallon, lbs.	8.3 lbs.
Consistency	Trowel
Cure Time (at recommended coverage rate)	4-8 hours to set, 24-48 hrs. to cure depending on surface and weather.
Application Temperature	50-120°F

### Approx. Shipping Weights: (Note: All approx. weights include container.)

5 gallons (18.9L)	48 lbs.
55 gallons (208.2L)	521 lbs.

## CAUTION! HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.

For exterior use only. Contains petroleum based products. Keep away from heat, sparks, and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, wash with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC = 250 g/l (2.1 lb./ gal) Maximum.

Description	CAS #
Asphalt	8052-42-4
Mineral Spirits	8052-41-3
Clay	1332-58-7
Cellulose	65996-61-4
Water	7732-18-5
Product is asbestos free. PATENT PENDING	

**LIMITED WARRANTY: Gardner-Gibson, Inc.** warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/ OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com