

2-9-06

Realex  
Division of United Industries  
P. O. Box 142642  
St. Louis, MO 63114-0642

Hazardous Material Identification System - (HMIS)	
HEALTH - 1	REACTIVITY - 0
FLAMMABILITY - 0	PERSONAL - Rubber gloves

# Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

**I Trade Name:** Real-Kill® Wasp & Hornet Killer

**Product Type:** Aerosol insecticide

**Product Item Number:** 10061.1      **Formula Code Number:**

EPA Registration Number	Manufacturer	Emergency Telephone Numbers
9688-117-478	Chemsico Division of United Industries Corporation 8494 Chapin Industrial Drive St. Louis, MO 63114	For Chemical Emergency: 1-800-633-2873 For Information: 1-800-332-5553 Prepared by: C. A. Duckworth Date Prepared: November 30, 2001

II Hazards Ingredient/Identity Information	III Physical and Chemical Characteristics																																										
<table border="1"> <thead> <tr> <th>Chemical</th> <th>%</th> <th>OSHA PEL</th> <th>ACGIH TLV</th> </tr> </thead> <tbody> <tr> <td>Heptane CAS# 142-82-5</td> <td>4.00</td> <td>400 ppm</td> <td>400 ppm</td> </tr> <tr> <td>Propylene glycol monobutyl ether CAS# 5131-66-8</td> <td>6.00</td> <td>None</td> <td>None</td> </tr> <tr> <td>Tralomethrin CAS# 66841-25-6</td> <td>0.01</td> <td>NA</td> <td>NE</td> </tr> <tr> <td>d-trans Allethrin CAS# 28057-48-9</td> <td>0.05</td> <td>NE</td> <td>NE</td> </tr> <tr> <td>Propane CAS# 74-98-6</td> <td>4.50</td> <td>1000 ppm</td> <td>NE</td> </tr> </tbody> </table>	Chemical	%	OSHA PEL	ACGIH TLV	Heptane CAS# 142-82-5	4.00	400 ppm	400 ppm	Propylene glycol monobutyl ether CAS# 5131-66-8	6.00	None	None	Tralomethrin CAS# 66841-25-6	0.01	NA	NE	d-trans Allethrin CAS# 28057-48-9	0.05	NE	NE	Propane CAS# 74-98-6	4.50	1000 ppm	NE	<table border="1"> <tbody> <tr><td><b>Appearance &amp; Odor:</b></td><td>Jet spray and a glycol ether odor.</td></tr> <tr><td><b>Boiling Point:</b></td><td>NA</td></tr> <tr><td><b>Melting Point:</b></td><td>NA</td></tr> <tr><td><b>Vapor Pressure:</b></td><td>110 psig at 54° C/130° F</td></tr> <tr><td><b>Specific Gravity:</b></td><td>0.97 (H<sub>2</sub>O = 1)</td></tr> <tr><td><b>Vapor Density:</b></td><td>Greater than 1 (Air = 1)</td></tr> <tr><td><b>% Volatile (by vol.):</b></td><td>95%</td></tr> <tr><td><b>Solubility in Water:</b></td><td>Greater than 87%</td></tr> <tr><td><b>Evaporation Rate:</b></td><td>Less than 1 (Butyl Acetate = 1)</td></tr> </tbody> </table>	<b>Appearance &amp; Odor:</b>	Jet spray and a glycol ether odor.	<b>Boiling Point:</b>	NA	<b>Melting Point:</b>	NA	<b>Vapor Pressure:</b>	110 psig at 54° C/130° F	<b>Specific Gravity:</b>	0.97 (H <sub>2</sub> O = 1)	<b>Vapor Density:</b>	Greater than 1 (Air = 1)	<b>% Volatile (by vol.):</b>	95%	<b>Solubility in Water:</b>	Greater than 87%	<b>Evaporation Rate:</b>	Less than 1 (Butyl Acetate = 1)
Chemical	%	OSHA PEL	ACGIH TLV																																								
Heptane CAS# 142-82-5	4.00	400 ppm	400 ppm																																								
Propylene glycol monobutyl ether CAS# 5131-66-8	6.00	None	None																																								
Tralomethrin CAS# 66841-25-6	0.01	NA	NE																																								
d-trans Allethrin CAS# 28057-48-9	0.05	NE	NE																																								
Propane CAS# 74-98-6	4.50	1000 ppm	NE																																								
<b>Appearance &amp; Odor:</b>	Jet spray and a glycol ether odor.																																										
<b>Boiling Point:</b>	NA																																										
<b>Melting Point:</b>	NA																																										
<b>Vapor Pressure:</b>	110 psig at 54° C/130° F																																										
<b>Specific Gravity:</b>	0.97 (H <sub>2</sub> O = 1)																																										
<b>Vapor Density:</b>	Greater than 1 (Air = 1)																																										
<b>% Volatile (by vol.):</b>	95%																																										
<b>Solubility in Water:</b>	Greater than 87%																																										
<b>Evaporation Rate:</b>	Less than 1 (Butyl Acetate = 1)																																										

IV Fire and Explosive Hazards Data	V Reactivity Data																										
<table border="1"> <tbody> <tr><td><b>Flash Point:</b></td><td>75° F (TCC) (liquid phase)</td></tr> <tr><td><b>Flame Extension:</b></td><td>0-inches (Level 1 Aerosol)</td></tr> <tr><td><b>Flammable Limits:</b></td><td>NA</td></tr> <tr><td><b>Autoignition Temperature:</b></td><td>NA</td></tr> <tr><td><b>Fire Extinguishing Media:</b></td><td>Water fog, Carbon dioxide, Dry chemical</td></tr> <tr><td><b>Decomposition Temperature:</b></td><td>NA</td></tr> <tr><td><b>Special Fire-Fighting Procedures:</b></td><td>Keep cans cool. Use equipment or shielding to protect personnel against bursting, rupturing or venting cans.</td></tr> <tr><td><b>Unusual Fire &amp; Explosion Hazards:</b></td><td>At elevated temperatures (over 54° C/130° F), cans may vent, rupture or burst. See Section V.</td></tr> </tbody> </table>	<b>Flash Point:</b>	75° F (TCC) (liquid phase)	<b>Flame Extension:</b>	0-inches (Level 1 Aerosol)	<b>Flammable Limits:</b>	NA	<b>Autoignition Temperature:</b>	NA	<b>Fire Extinguishing Media:</b>	Water fog, Carbon dioxide, Dry chemical	<b>Decomposition Temperature:</b>	NA	<b>Special Fire-Fighting Procedures:</b>	Keep cans cool. Use equipment or shielding to protect personnel against bursting, rupturing or venting cans.	<b>Unusual Fire &amp; Explosion Hazards:</b>	At elevated temperatures (over 54° C/130° F), cans may vent, rupture or burst. See Section V.	<table border="1"> <tbody> <tr><td><b>Stability:</b></td><td>Stable</td></tr> <tr><td><b>Polymerization:</b></td><td>Will not occur</td></tr> <tr><td><b>Conditions to Avoid:</b></td><td>Temperatures over 130° F</td></tr> <tr><td><b>Incompatible Materials:</b></td><td>NA</td></tr> <tr><td><b>Hazardous Decomposition or Byproducts:</b></td><td>Carbon dioxide, carbon monoxide</td></tr> </tbody> </table>	<b>Stability:</b>	Stable	<b>Polymerization:</b>	Will not occur	<b>Conditions to Avoid:</b>	Temperatures over 130° F	<b>Incompatible Materials:</b>	NA	<b>Hazardous Decomposition or Byproducts:</b>	Carbon dioxide, carbon monoxide
<b>Flash Point:</b>	75° F (TCC) (liquid phase)																										
<b>Flame Extension:</b>	0-inches (Level 1 Aerosol)																										
<b>Flammable Limits:</b>	NA																										
<b>Autoignition Temperature:</b>	NA																										
<b>Fire Extinguishing Media:</b>	Water fog, Carbon dioxide, Dry chemical																										
<b>Decomposition Temperature:</b>	NA																										
<b>Special Fire-Fighting Procedures:</b>	Keep cans cool. Use equipment or shielding to protect personnel against bursting, rupturing or venting cans.																										
<b>Unusual Fire &amp; Explosion Hazards:</b>	At elevated temperatures (over 54° C/130° F), cans may vent, rupture or burst. See Section V.																										
<b>Stability:</b>	Stable																										
<b>Polymerization:</b>	Will not occur																										
<b>Conditions to Avoid:</b>	Temperatures over 130° F																										
<b>Incompatible Materials:</b>	NA																										
<b>Hazardous Decomposition or Byproducts:</b>	Carbon dioxide, carbon monoxide																										

VI Health Hazard Data	VII Precautions for Safe Handling and Use														
<table border="1"> <tbody> <tr><td><b>Eye Contact:</b></td><td>Causes eye irritation. Avoid contact with eyes. <b>First Aid:</b> Flush eyes with plenty of water. Call a physician if irritation persists.</td></tr> <tr><td><b>Special Notes:</b></td><td>Avoid contamination of food and drinking water.</td></tr> <tr><td><b>Health conditions Aggravated by Exposure:</b></td><td>None known</td></tr> <tr><td><b>Ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens:</b></td><td>None</td></tr> </tbody> </table>	<b>Eye Contact:</b>	Causes eye irritation. Avoid contact with eyes. <b>First Aid:</b> Flush eyes with plenty of water. Call a physician if irritation persists.	<b>Special Notes:</b>	Avoid contamination of food and drinking water.	<b>Health conditions Aggravated by Exposure:</b>	None known	<b>Ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens:</b>	None	<table border="1"> <tbody> <tr><td><b>Steps to be Taken in Case Material is Released or Spilled:</b></td><td>Avoid breathing vapors. Avoid contact with liquid. Remove ignition sources. Soak up spills with absorbent material.</td></tr> <tr><td><b>Waste Disposal:</b></td><td>Do not puncture or incinerate containers. Give empty, leaking or full containers to a facility qualified to dispose of pressurized containers.</td></tr> <tr><td><b>Handling &amp; Storage Precautions:</b></td><td>Do not store where temperatures can exceed 54° C/130° F.</td></tr> </tbody> </table>	<b>Steps to be Taken in Case Material is Released or Spilled:</b>	Avoid breathing vapors. Avoid contact with liquid. Remove ignition sources. Soak up spills with absorbent material.	<b>Waste Disposal:</b>	Do not puncture or incinerate containers. Give empty, leaking or full containers to a facility qualified to dispose of pressurized containers.	<b>Handling &amp; Storage Precautions:</b>	Do not store where temperatures can exceed 54° C/130° F.
<b>Eye Contact:</b>	Causes eye irritation. Avoid contact with eyes. <b>First Aid:</b> Flush eyes with plenty of water. Call a physician if irritation persists.														
<b>Special Notes:</b>	Avoid contamination of food and drinking water.														
<b>Health conditions Aggravated by Exposure:</b>	None known														
<b>Ingredients listed by NTP, OSHA, or IARC as Carcinogens or Potential Carcinogens:</b>	None														
<b>Steps to be Taken in Case Material is Released or Spilled:</b>	Avoid breathing vapors. Avoid contact with liquid. Remove ignition sources. Soak up spills with absorbent material.														
<b>Waste Disposal:</b>	Do not puncture or incinerate containers. Give empty, leaking or full containers to a facility qualified to dispose of pressurized containers.														
<b>Handling &amp; Storage Precautions:</b>	Do not store where temperatures can exceed 54° C/130° F.														

VIII Control Measures	IX Transportation Data				
Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.	<table border="1"> <tbody> <tr><td><b>DOT Shipping Name:</b></td><td>Consumer Commodity</td></tr> <tr><td><b>DOT Hazard Class:</b></td><td>ORM-D</td></tr> </tbody> </table>	<b>DOT Shipping Name:</b>	Consumer Commodity	<b>DOT Hazard Class:</b>	ORM-D
<b>DOT Shipping Name:</b>	Consumer Commodity				
<b>DOT Hazard Class:</b>	ORM-D				

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.